

Technical Data Sheet



Product: S- 4608 MF

Product Description: Double sided tape

Adhesive: MF-adhesive is a modified polyacrylate and has good, all-round adhesive properties especially with reference to ageing and weathering properties. It has very good initial tack with very high peel adhesion to a wide variety of low surface energy substrates such as foams, PE, PP and EPDM. MF-adhesive is an ideal lamination adhesive for a wide variety of laminates.

Product structure:

Support	PES/PVA scrim
Interliner	Release paper, yellow, 90 g/m ²
Adhesive weight	70 g/m ²
Total thickness	0,08 mm

Characteristics:

Temperature resistance (according to the ATP test method AA-B-12-07)	from -40 °C to +90 °C
Adhesive strength (According to AFERA 5001)	min 18 N/25 mm Contact time: 1 h

Note:

All our products are subjected to a strict quality control by our QM-System, which is in accordance with ISO/TS 16949, DIN EN ISO 9001 and DIN EN ISO 14001. The information is based on our present knowledge and our experience. Because of the large number of possible influences during the processing and application of our products, this information does not release the user from the obligation to conduct his own tests and trials. Users of our products are responsible for observing any patent rights that may exist and for following existing regulations. Our applications technology section is always pleased to give advice about suitability tests on original materials.

Last modification:
B. / 2010-11-11

