

Technical Data Sheet



Product: S- 4710 AG

Product Description: Double sided tape

Adhesive: The AG-adhesive is a pure polyacrylic with excellent ageing resistance, especially in terms of long term performance such as weathering and UV-resistance. It provides a superior combination of very high adhesion and exceptional cohesion with good tack performance. AG-adhesive also possesses very good adhesion to low surface energy substrates such as foams, PE and PP filmic products. It has exceptionally low emissions determined by VOC and fogging. The unique all round performance of AG adhesive confirms its suitability for many demanding applications, especially for the automotive industry.

Product structure:

Support	No support, transfer tape
Interliner	Release paper, yellow, 90 g/m ²
Adhesive weight	100 g/m ²
Total thickness	0,10 mm

Characteristics:

Temperature resistance (according to the ATP test method AA-B-12-07)	from -40 °C to +200 °C
Adhesive strength (According to AFERA 5001)	min 25 N/25 mm Contact time: 24 h

Note:

All our products are subjected to a strict quality control by our QM-System, which is in accordance with ISO/TS 16949, DIN EN ISO 9001 and DIN EN ISO 14001. The information is based on our present knowledge and our experience. Because of the large number of possible influences during the processing and application of our products, this information does not release the user from the obligation to conduct his own tests and trials. Users of our products are responsible for observing any patent rights that may exist and for following existing regulations. Our applications technology section is always pleased to give advice about suitability tests on original materials.

Last modification:
B. / 2011-08-31